

FCI Aerospace Division

Pressure Switch Series: Model AS-PS

Aerospace and Military Applications



FCI'S Technology Advantage

FCI is a world market leader in sensors for use in the aerospace, military, industrial and process control services. Precision, highly reliable and repeatable sensing includes pressure, temperature, liquid and gas flow, and liquid level.

Sensing Technology

FCI pressure elements use piezoresistive sensors (strain gage sensors) fabricated using silicon processing techniques common in the semiconductor industry.

Piezoresistive sensors are often referred to as IC sensors (integrated circuit), solid state sensors, monolithic sensors (formed from single crystal silicon) or just silicon sensors.

FCI elements consist of four strain sensitive resistors implanted into silicon wafers. These resistors are connected in a wheatstone bridge configuration. Two resistors increase in ohmic value as pressure increases while the other two decrease.

When pressure is applied, the resistors in the arms of the bridge change by an amount ΔR . Alignment of the resistors on the silicon determines which resistors increase and which decrease with pressure.

Processing Technology

A special purpose, RISC, fixed program, microcontroller is the basic processing circuit. Temperature compensation, linearization and output switch point are controlled by the processor.

Pressure Element Applications

FCI Aerospace Division Pressure Elements meet the demanding requirements of aerospace and military customers with full qualification compliance, while maintaining the flexibility and capability necessary to meet the special needs of a variety of applications, including:

- » Fuel
- » Hydraulics
- » ECS
- » Coolant Systems
- » Lubrication

FCI's Aerospace design team uses the latest in computer aided engineering technology and has access to FCI's extensive test and calibration facilities to fully analyze and test sensor under a variety of conditions. Custom designs are available for any application. FCI fully tests each sensor to your requirements before shipping them to you. After all, we strive to continually meet and exceed our customer expectations and requirements for products and services.

FCI's Pressure Element Features

- » No Moving Parts
- » High Reliability
- » Wide Range
- » Simple Installation
- » Durable Sensor Solution
- » Military Standard Connections
- » Corrosion and Abrasion Resistance
- » Multiple Switch Points, Up to 3
- » Linear Voltage Output
- » Available Temperature Option

Visit FCI Aerospace Division on the Web: www.fluidcomponents.com

1755 La Costa Meadows Drive, San Marcos, California 92078 USA Phone 760-744-6950 800-854-1993 Fax 760-736-6250
European Office: Persephonestraat 3-01 5047 TT Tilburg The Netherlands Phone 31-13-5159989 Fax 31-13-5799036

FCI Aerospace Division

Pressure Switch Series: Model AS-PS

Specifications

Service: Pressure monitoring of liquid and gas

Material of Construction: All-welded, 300 series stainless steel, aluminum, titanium or other alloys optionally available with hermetically sealed connectors.

Electrical Connection: Military, commercial connector or pigtail cable.

Process Connection: Threaded or flanged:
AS930-03
AS4395E8
MS33656E8

Pressure Performance Properties:

Operating Pressure Ranges	Proof Pressure	Burst Pressure
0 - 3 psig	9 psig	15 psig
0 - 10 psig	30 psig	50 psig
0 - 30 psig	90 psi	150 psi
0 - 100 psi	300 psi	500 psi
0 - 500 psi	1200 psi	2400 psi

Accuracy:

Repeatability: $\pm 0.1\%$ of reading
Interchangeability: $\pm 1\%$ of reading

Weight: .2 lbs - .7 lbs

Temperature Environment:

Operating Temperature: -40°C to 125°C
Survival Temperature: -80°C to 200°C

Time Constant: .5 Seconds

Electrical Parameters:

Input Current <10 mA
I.R. Test Voltage <1000 VDC
D.R. Test Voltage³ <500 VDC
Bonding <2.5 milliohms

Environmental Parameters:

Altitude: 100,000 ft
Humidity: 100%
Thermal Shock: 10°C/min.
Vibration: Rotary/Fixed Wing
Acceleration: 10 gs


Output with 28 VDC input	Open-leakage μA	Close-sink μA - 800mA
	On pressure rise (Ps \pm 1psi)	On pressure decline (Ps+ Ph \pm 1psi)

Qualification:

MIL-STD-130
MIL-STD-810
MIL-STD-889
MIL-STD-461/462

Marking
Environmental Testing
Dissimilar Metals
EMI

Quality System Approval: ISO 9001, AS 9000




CONNECTOR PIN-OUT	
CONN PIN	
A	+IN
D	-IN
B	+OUT
C	-OUT
E & F	SPARES

NOTE: MATING CONNECTOR PLUG MUST ALLOW GAGE HOLE TO VENT (GAGE UNITS ONLY REMOVE O-RING).

DIMENSIONS IN BRACKETS [] ARE IN MILLIMETERS.

Typical Pressure Switch with Electrical Connector



WIRING	
COND COLOR	
RED	+IN
BLACK	-IN
GREEN	+OUT
WHITE	-OUT
BARE	SHIELD

DIMENSIONS IN BRACKETS [] ARE IN MILLIMETERS.

Typical Pressure Switch with Pigtail Cable



Visit FCI Aerospace Division on the Web: www.fluidcomponents.com

1755 La Costa Meadows Drive, San Marcos, California 92078 USA Phone 760-744-6950 800-854-1993 Fax 760-736-6250
European Office: Persephonestraat 3-01 5047 TT Tilburg The Netherlands Phone 31-13-5159989 Fax 31-13-5799036